

RECLAIMED AMERICAN HARDWOODS - AMERICAN GOTHIC

Reclaimed Oak, Red Oak**, White Oak**, Hickory, Beech, Grey Elm, Maple, Chestnut, Red Elm, Cherry, Walnut & Autumn Woods

DENSITY

No limit on grain density

HEARTWOOD

No limit on combination of heartwood and sapwood

GRAIN

A mixture of flat-sawn and vertical grain

COLOR

No restriction on natural color variation

KNOTS

No limitation on sound knots. Surface defects resulting from unsound knots will be present.

TEXTURE

Re-sawing and milling removes all but infrequent saw marks and previous wear patterns.

HOLES

Nail and other mechanical holes can be present and occasionally reach 3/8" in diameter. Surface defects from insect marks, including pin holes will be present.

DISCOLORATION

Ferrous staining from previous fasteners may be present.

CHECKS

Checks and crack allowed to 3/32" in widths 7" and below. In wider widths these sizes increase.

LENGTHS

2' - 12' is standard, 5' - 7' average

* Grading applies to flooring and boardstock, all material graded best face.

**This specification guarantees 90% of the called specie with an allowance of up to 10% of the other specie.

PIONEER MILLWORKS

1180 COMMERCIAL DRIVE :: FARMINGTON NY 14425 :: (800) 951-9663

FAX (585) 924-9962 :: www.pioneermillworks.com :: jered@pioneermillworks.com